Project/Job Name:

Location:

Fixture Type:

Notes:

S21413 - 14 Watt LED PL; CCT Selectable; Lumens Selectable; Type B; Ballast Bypass; White Finish; 120-277 Volt

- CCT Selectable

ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1750L-1820L
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Warm White to Natural Light
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	26W
Operating Temperature :	-13F to +122F (-25C to +50C)
Ballasting Requirements :	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
THD:	20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PHYSICAL

Base:	G24d (2-Pin)
Shape:	PL
Finish:	White
Dimensions (In.):	MOL: 5.89 - MOD: 1.95
Weight (Lbs.):	0.4
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923215728
Each Quantity:	1
Each Dimensions:	2.56 x 2.36 x 7.17

INFO

Installation Note:	Suggested wattage equivalency = 26W CFL
Min Compartment Size:	Length: 6 in. Width: 6 in. Height: 8.5 in.

© Satco Products, Inc.
All rights reserved 2026

ACCESSORIES

	80-973	Emergency Driver Enclosure; For use with S8000 and S8002
	80-987	Emergency Remote Test Switch; Single Gang Plate; White Finish
	S8000	5 Watt LED Emergency Driver; 120-277 Volts
	S8002	10 Watt LED Emergency Driver; 120-277 Volt

© Satco Products, Inc.
All rights reserved 2026