



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11851 - 15 Watt Commercial LED Downlight; 6 in.; CCT Adjustable; 120-277 volt; Econo

- CCT Selectable
- IC Rated
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	1600L
CRI:	80+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm to Cool White
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 20 percent
Dimming Type :	0-10V Dimming
Incandescent Equivalent :	75W
Operating Temperature :	-4F to +104F (-20C to +40C)
Replaceable Light Source :	No
Power Factor :	0.99
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923118517
Each Quantity:	1
Each Dimensions:	7.87 x 3.94 x 9.05

INFO

Installation Note:	J-box required but not included
--------------------	---------------------------------

PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions:	H:3.46" DIA:7.40"
Weight (Lbs.):	1.05
Material:	Aluminum

INSTALLATION

Ceiling Aperture:	6.02 in. Cutout
Max Drywall Thickness:	0.38 to 1.25 in.
Sloped Ceiling Compatible:	Yes
Can Size:	6 in.

COMPLIANCE

Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	3893922
Energy Star Lamp Category:	Downlight Recessed
DLC Approved:	No
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

**80-944**New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter

**80-959**Rough-In Mounting Plate for 4/6/8 or 10 in. Commercial Downlight Fixtures

**80-973**Emergency Driver Enclosure; For use with S8000 and S8002

**80-987**Emergency Remote Test Switch; Single Gang Plate; White Finish

**S13541**6" Flat Goof Ring for Commercial Downlights, Round, White Finish, 10.00 OD, 6.00 ID, 0.032 Thick.

**S8000**5 Watt LED Emergency Driver; 120-277 Volts

**S8002**10 Watt LED Emergency Driver; 120-277 Volt



S11851 - 15 Watt Commercial LED Downlight; 6 in.; CCT Adjustable; 120-277 volt; Econo

DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Lutron	RMJS-8T-DV-B + PJ2-3BRL-GWH-L01
Eaton	SF10P