



PAR30LN



PAR38

CAPSYLITE® PAR30 LONG NECK

Suitable for use in unshielded fixtures.

			Product	Symbols &		Pkg	Beam	Class &	Avg	Lumens		Beam	MOL				
Watts	Bulb	Base	Number	Footnotes	Ordering Abbreviation	Volts	Qty	Type	Filament	Rated Life(hrs)	CCT	CBCP	Angle	(in)			
50	PAR30LN	E26 Med	14482	★     43,73,118,134,137,162 @ 120 volts, approximate 44 watts, 500 lumens, 5000 hours	50PAR30LN/HA/NSP9	130	15	NSP	C,CC-8	2500	660 2850	7000	10	4.63			
			14520	★     43,73,118,134	50PAR30LN/HA/NFL25	120	15	NFL	C,CC-8	2500	660 2850	2100	25	4.63			
			14822	★     43,73,118,134	50PAR30LN/HA/NFL	120	6	NFL	C,CC-8	2500	660 2850	2100	25	4.63			
			14478	★     43,73,118,134,137,162 @ 120 volts, approximate 44 watts, 500 lumens, 5000 hours	50PAR30LN/HA/NFL25	130	15	NFL	C,CC-8	2500	660 2850	2100	25	4.63			
			14537	★     43,73,118,134	50PAR30LN/HA/WFL50	120	15	WFL	C,CC-8	2500	660 2850	660	50	4.63			
			14536	★     43,73,118,134	50PAR30LN/HA/WFL	120	6	WFL	C,CC-8	2500	660 2850	660	50	4.63			
			14486	★     43,73,118,134,137,162 @ 120 volts, approximate 44 watts, 500 lumens, 5000 hours	50PAR30LN/HA/WFL50	130	15	WFL	C,CC-8	2500	660 2850	660	50	4.63			
			15419	★     43,73,118,134,137,162 @ 120 volts, approximate 44 watts, 500 lumens, 5000 hours	50PAR30LN/HA/WFL50/CVP	130	6	WFL	C,CC-8	2500	660 2850	660	50	4.63			
			75	PAR30LN	E26 Med	14786	★     43,73,118	75PAR30LN/HA/NSP9	120	15	NSP	C,CC-8	2500	1130 2950	12000	10	4.63
						14777	★     43,73,118,137,182 @ 120 volts, approximate 66 watts, 860 lumens, 5000 hours	75PAR30LN/HA/NSP9	130	15	NSP	C,CC-8	2500	1130 2900	12000	10	4.63
14769	★     43,73,118	75PAR30LN/HA/NFL25				120	15	NFL	C,CC-8	2500	1130 2900	3600	25	4.63			
14824	★     43,73,118	75PAR30LN/HA/NFL				120	6	NFL	C,CC-8	2500	1130 2900	3600	25	4.63			
14778	★     43,73,118,137,182 @ 120 volts, approximate 66 watts, 860 lumens, 5000 hours	75PAR30LN/HA/NFL25				130	15	NFL	C,CC-8	2500	1130 2900	3600	25	4.63			
14768	★     43,73,118	75PAR30LN/HA/WFL50				120	15	WFL	C,CC-8	2500	1130 2900	1100	50	4.63			
14823	★     43,73,118	75PAR30LN/HA/WFL				120	6	WFL	C,CC-8	2500	1130 2900	1100	50	4.63			
14785	★     43,73,118,137,182 @ 120 volts, approximate 66 watts, 860 lumens, 5000 hours	75PAR30LN/HA/WFL50				130	15	WFL	C,CC-8	2500	1130 2900	1100	50	4.63			
15418	★     43,73,118,137,182 @ 120 volts, approximate 66 watts, 860 lumens, 5000 hours	75PAR30LN/HA/WFL50/CVP				130	6	WFL	C,CC-8	2500	1130 2900	1100	50	4.63			

CAPSYLITE IR® PAR38

Halogen PAR lamp with infrared reflective coating on the lamp capsule. Suitable for use in unshielded fixtures.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	CBCP	Beam Angle	MOL (in)
50	PAR38	E26 Med Skt	13973	★☐☐☐ 43,47,72,118	50PAR38/CAPIR/DAY/WSP12	120	15	WSP	C,CC-8	3000	700 2875	7000	12	5.31
			15259	★☐☐☐ 43,47,72,118	50PAR38/CAPIR/DAY/FL30	120	15	FL	C,CC-8	3000	700 2875	1800	30	5.31