



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**67-121** - Combination Red Exit Sign/Emergency Light, 90min Ni-Cad backup, 120/277V, Dual Head, Single/Dual Face, Universal Mounting; White Finish

- Has Emergency Battery



### ELECTRICAL

|                            |                                 |
|----------------------------|---------------------------------|
| Technology:                | LED                             |
| Watts:                     | 2.8W                            |
| Volts:                     | 120V/277V                       |
| Lumens:                    | 150L                            |
| Lamp Base :                | Integrated - Integrated         |
| CRI:                       | 70+                             |
| CCT (Kelvins):             | 5700K -                         |
| Dimmable:                  | Non-Dimmable -                  |
| Incandescent Equivalent :  | 25W                             |
| Operating Temperature :    | +50F to +104F (+10C to +40C)    |
| Lamp Included :            | Integrated                      |
| Number of Lamps :          | 2                               |
| Replaceable Light Source : | No                              |
| Surge Protection :         | Built-in surge protection - 3KV |
| Voltage Type:              | AC Only; Dual Voltage           |
| Warranty:                  | 2-Years                         |

### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923675751        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 15.98 x 7.56 x 3.43 |

### INFO

|                     |                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Info:    | Input Wattage: 2.8W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 2.8W                                                                                             |
| Specification Note: | UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft |
| Includes:           | Mounting hardware and accessories                                                                                                                                            |


### PHYSICAL

|                |                          |
|----------------|--------------------------|
| Finish:        | White                    |
| Lens Finish:   | Clear                    |
| Lens Material: | Polycarbonate (PC)       |
| Dimensions:    | W:19.00" H:7.25" D:4.00" |
| Weight (Lbs.): | 2.99                     |
| Material:      | Thermo Plastic           |
| Depth:         | 4                        |

### COMPLIANCE

|                  |                                   |
|------------------|-----------------------------------|
| Safety Listing:  | cULus - Certified; cULus - Listed |
| Location Rating: | Damp                              |
| Indoor/Outdoor:  | Indoor                            |
| DLC Approved:    | No                                |
| CA Prop 65:      | Lead                              |
| BAA Compliant:   | No                                |
| FCC Compliant:   | Yes                               |
| RoHS Compliant:  | Yes                               |
| Restrictions:    | No Restrictions                   |

## ACCESSORIES

|                                                                                    |               |                                                                                                                                                   |
|------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
|    | <b>67-900</b> | Pendant suspension mounting kit including one 1/4IPS x 12in long white threaded stem, one 4-3/8in round white swivel canopy cover and lock nuts   |
|    | <b>67-901</b> | Pendant suspension mounting kit including one 1/4IPS x 12in long black threaded stem, one 4-3/8in round black swivel canopy cover and lock nuts   |
|    | <b>67-902</b> | Pendant suspension mounting kit including one 1/4IPS x 12in long silver threaded stem, one 4-3/8in round silver swivel canopy cover and lock nuts |
|    | <b>67-910</b> | Pendant suspension extension kit including one 1/4IPS x 6in long white threaded stem, one 1/4IPS coupler                                          |
|    | <b>67-911</b> | Pendant suspension extension kit including one 1/4IPS x 6in long black threaded stem, one 1/4IPS coupler                                          |
|    | <b>67-912</b> | Pendant suspension extension kit including one 1/4IPS x 6in long silver threaded stem, one 1/4IPS coupler                                         |
|    | <b>67-915</b> | Pendant suspension extension kit including one 1/4IPS x 12in long white threaded stem, one 1/4IPS coupler                                         |
|   | <b>67-916</b> | Pendant suspension extension kit including one 1/4IPS x 12in long black threaded stem, one 1/4IPS coupler                                         |
|  | <b>67-917</b> | Pendant suspension extension kit including one 1/4IPS x 12in long silver threaded stem, one 1/4IPS coupler                                        |



**67-121** - Combination Red Exit Sign/Emergency Light, 90min Ni-Cad backup, 120/277V, Dual Head, Single/Dual Face, Universal Mounting; White Finish

**ACCESSORIES**

|                         |        |
|-------------------------|--------|
| Pendant Conversion Kit: | 67-902 |
|-------------------------|--------|