



PAR30



PAR30LN

CAPSYLITE® PAR30

Suitable for use in unshielded fixtures.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	CBCP	Beam Angle	MOL (in)
50	PAR30	E26 Med	14526	★ 43,118	50PAR30/HAL/NSP9	120	15	NSP	C,CC-8	2500	660 2850	8800	9	3.63
			14530	★ 43,118,137,162	50PAR30/HAL/NSP9	130	15	NSP	C,CC-8	2500	660 2850	8800	9	3.63
			@ 120 volts, approximate 44 watts, 500 lumens, 5000 hours											
			14527	★ 43,118	50PAR30/HAL/NFL25	120	15	NFL	C,CC-8	2500	660 2850	2300	25	3.63
			14531	★ 43,118,137,162	50PAR30/HAL/NFL25	130	15	NFL	C,CC-8	2500	660 2850	2300	25	3.63
			@ 120 volts, approximate 44 watts, 500 lumens, 5000 hours											
			14710	★ 43,118	50PAR30/HAL/FL40	120	15	FL	C,CC-8	2500	660 2850	1300	40	3.63
60	PAR30	E26 Med	14533	★ 43,118,137,162	50PAR30/HAL/FL40	130	15	FL	C,CC-8	2500	660 2850	1300	40	3.63
			@ 120 volts, approximate 44 watts, 500 lumens, 5000 hours											
			14332	★ 43,118	60PAR30/HAL/NSP9	120	15	NSP	C,CC-8	3000	860 2875	12000	9	3.63
			14333	★ 43,118	60PAR30/HAL/NFL25	120	15	NFL	C,CC-8	3000	860 2875	2775	25	3.63
			14090	★ 43,90,118,137	60PAR30/HAL/NFL25	130	15	NFL	C,CC-8	3000	860 2875	2775	25	3.63
75	PAR30	E26 Med	@ 120 volts, approximate 53 watts, 660 lumens, 6000 hours.											
			14084	★ 43,90	60PAR30/HAL/FL40	130	15	FL	C,CC-8	3000	860 2875	1550	40	3.63
			@ 120 volts, approximate 53 watts, 660 lumens, 6000 hours.											
			14604	★ 43,118	75PAR30/HAL/NSP9	120	15	NSP	C,CC-8	2500	1130 2900	15400	9	3.63
			14628	★ 43,118,137,182	75PAR30/HAL/NSP9	130	15	NSP	C,CC-8	2500	1130 2900	15400	9	3.63
			@ 120 volts, approximate 66 watts, 860 lumens, 5000 hours											
			14603	★ 43,118	75PAR30/HAL/NFL25	120	15	NFL	C,CC-8	2500	1130 2900	4000	25	3.63
			14627	★ 43,118,137,182	75PAR30/HAL/NFL25	130	15	NFL	C,CC-8	2500	1130 2900	4000	25	3.63
			@ 120 volts, approximate 66 watts, 860 lumens, 5000 hours											
			14606	★ 43,118	75PAR30/HAL/FL40	120	15	FL	C,CC-8	2500	1130 2900	2100	40	3.63
			14629	★ 43,118,137,182	75PAR30/HAL/FL40	130	15	FL	C,CC-8	2500	1130 2900	2100	40	3.63
			@ 120 volts, approximate 66 watts, 860 lumens, 5000 hours											

CAPSYLITE® PAR30 LONG NECK

Suitable for use in unshielded fixtures.

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Beam Type	Class & Filament	Avg Rated Life(hrs)	Lumens CCT	CBCP	Beam Angle	MOL (in)
35	PAR30LN	E26 Med	14759	★ 43,73,118	35PAR30LN/HAL/NSP9	120	15	NSP	C,CC-8	2500	450 2775	4500	10	4.63
			14764	★ 43,73,118	35PAR30LN/HAL/WFL50	120	15	WFL	C,CC-8	2500	450 2775	450	50	4.63
50	PAR30LN	E26 Med	14509	★ 43,73,118,134	50PAR30LN/HAL/NSP9	120	15	NSP	C,CC-8	2500	660 2850	7000	10	4.63