



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11801R1 - 9 Watt LED Downlight Retrofit; 5-6 Inches; CCT Selectable; Round; White Finish; 120 Volt

- Air Tight
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	800L
CRI:	90+
R9 Value :	51
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Forward (TRIAC) or Reverse Phase; 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase Cut (TRIAC); 120V only
Incandescent Equivalent :	65W
Operating Temperature :	-4F to +104F (-20C to +40C)
Replaceable Light Source :	No
Connection:	Connector or Adapter
Power Factor :	0.9
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923947766
Each Quantity:	1
Each Dimensions:	7.60 x 2.36 x 8.46

INFO

Installation Note:	Can size minimum diameter: 5.36"; minimum height: 7.5"
Includes:	E26 Adapter included (S9001)

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions:	H:2.32" DIA:7.40"
Weight (Lbs.):	0.63
Material:	Steel

INSTALLATION

Ceiling Aperture:	5.36 in. Cutout
Can Size:	5-6 in.

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4587324
Energy Star Lamp Category:	Downlight Solid State Retrofit
DLC Approved:	No
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES**80-2676** Pressure Bracket kit for 5/6-Inch Downlight Retrofits, set of two brackets**80-868** QC to E26 Socket Whip for Downlight Cans; Temp Light Adapter Cable**80-982** 5 Inch Recessed Can; For New Construction**80-983** 5 Inch Recessed Can; For Remodeling**80-988** 6 Inch Recessed Can; For New Construction**80-989** 6 Inch Recessed Can; For Remodeling**80-996** DLR Air Tight Foam Gasket; White Finish; 12-Pack**S12621** Friction Band for 5/6 Inch Downlight Retrofit; Adapter for Oversized Can**S8999** GU24 Socket Adapter For Recessed Down Light**S9000** GU10 Socket Adapter For Recessed Down Light



S11801R1 - 9 Watt LED Downlight Retrofit; 5-6 Inches; CCT Selectable; Round; White Finish; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Leviton	66DF-10W
Leviton	66ELV
Satco	86/103
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSE06-10Z
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10
Eaton	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVCL-253P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQRA-PRO
Lutron	HQRD-10D

Lutron	HQRD-10NBD
Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL
Lutron	HQRD-PRO
Lutron	HRST-PRO-N
Leviton	IPL06
Lutron	LECL-153P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MRF2S-6ELV
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10NXD
Lutron	PD-5NE
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-10D
Lutron	RRD-6CL
Lutron	RRD-6ND
Lutron	RRD-H6BRL
Lutron	RRD-PRO
Lutron	RRST-PRO-N

Satco	S11268
Eaton	SAL06P
Lutron	SCL-153P
Lutron	ST-PRO-N
Lutron	STCL-153M
Eaton	SUF7
Eaton	TAL06P-C2
Lutron	TGCL-153PH
Leviton	TSL06
Leviton	TSM10
Lutron	TTCL-100H
Eaton	VSUL06D
Acuity	WSX-PDT-WH
Legrand	WWRL50WH