

Version	2.1	Date	1/26/25
Prepared By	JC		


PRODUCT SPECIFICATION			
Category	Backlit Panel		
Item Number	9669		
Stock Code	PNL40S/2x2/8C3-PK2 (2pcs/pk)		
Mounting	T-Grid Ceiling, Surface Mount, Suspend Mount Kit, Flange Mount Kit		
Housing Color	White		
PICTURE			

ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	20/30/40	Replacement Wattage (W)	90-100
Tested Wattage (W)	20/30/40		
Input Voltage (V)	120-277V	Surge Protect Level	2.5KV
Voltage Frequency (Hz)	50/60		
Input Current (A)	0.34 (max)	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	Yes
THD	<20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	2,200	CCT (K)	3CCT (35/40/50K)
	3,300		
	4,400		
Efficacy (lm/w)	110	Beam Angle (°)	115°
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4°F ~ 104°
Storage Temperature (°F)	-4°F ~ 176°
IP Rating	Damp Location
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
K7338332	FXPNL-BAEM-MT2FT-BLP-PK2	LED Emergency Driver for 100-277V for 2x2/2x4 Back-Lit Panel with a mounting plate for 9669 and 9670
P10588	MT-2x2BOX-2.25in	2.25" Height 2x2 Surface Mount Kit for Back-Lit Panel
P10417	MT-2X2BOX-3.0IN	3.0" Height 2x2 Surface Mount Kit for Back-Lit Panel / Troffer
P10335	MT-2x2BOX-4.5in	4.5" Height 2x2 Surface Mount Kit for Back-Lit Panel / Troffer
P10228	MT-2X2FMBOX	2x2 Flange Mount Kit for Back-Lit Panel / Troffer

PRODUCT DIMENSIONS			
Width- in / (mm)	23.74"	603	
Height- in / (mm)	23.70"	603	
Depth- in / (mm)	1.42"	36	
IK Rating	-		
Weight (lbs)	4.11		
Mounting Height (ft)	6~20		
Cable Length (ft)	-		

CERTIFICATIONS			
UL/ETL	UL,cUL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS