

How to Use Your Catalog

APPLICATION ICONS

							
AMUSEMENT	CEILING FAN	CEILING FIXTURE	CHANDELIER	COMMERCIAL	INDUSTRIAL	LANDSCAPE	OUTDOOR COMMERCIAL
							
OUTDOOR RESIDENTIAL	PENDANT/ DOWNLIGHTS	PORTABLE	RECESSED	SIGN/DISPLAY	TRACK	VANITY	WALL MOUNT/ SCONCE

SPECIFICATION TABLE

Energy efficient lamp alternatives		Indicates minimum sell quantity (inner) and smallest shipping carton (master)		Measurement of brightness		Average life expressed in hours		Brightness at the center of the beam		Maximum overall length in inches		Footnotes can be found on the last page of each section	
For LED alternatives, see Bulbrite's LED catalog.													

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner/ Master	Beam	Color Temp.	Lumens	Average Hours	CBCP	M.O.L.	Notes pg. 95
20	MR16	GU5.3	646320	BAB/24	24	10 / 50	Flood 36°	2900K	260	2000	405	1.875"	1,2,4
			620020	BAB/120	120	10 / 50	Flood 36°	2900K	130	2000	160	1.875"	2,4
			620320	BAB/GY8	120	10 / 50	Flood 36°	2900K	130	2000	160	1.875"	2,4
35	MR16	GU5.3	646135	FRB/24	24	10 / 50	Spot 12°	2900K	370	2000	3600	1.875"	D,1,2,4
			646335	FMW/24	24	10 / 50	Flood 36°	2900K	420	2000	1000	1.875"	1,2,4
			620035	FMW/120	120	10 / 50	Flood 36°	2900K	320	2000	360	1.875"	2,4
50	MR16	GU5.3	620335	FMW/GY8	120	10 / 50	Flood 36°	2900K	320	2000	360	1.875"	2,4
			646150	EXT/24	24	10 / 50	Spot 12°	2900K	710	2000	6000	1.875"	1,2,4
			646350	EXN/24	24	10 / 50	Flood 36°	2900K	750	2000	1845	1.875"	1,2,4
			620050	EXN/120	120	10 / 50	Flood 36°	2900K	560	2000	600	1.875"	2,4
		GY8	620350	EXN/GY8	120	10 / 50	Flood 36°	2900K	560	2000	600	1.875"	2,4

MR16

GU5.3, GY8 - 24V, 120V

- Provides UV protection
- Filament types include CC-2V and CC-8
- Ideal for general residential and commercial applications



**MR16 24V
GU5.3 BASE**

W/ LENS
BAB/24
FMW/24
FRB/24
EXN/24
EXT/24

**MR16 120V
GU5.3 BASE**

W/ LENS
BAB/120
FMW/120
EXN/120



**MR16 120V
GY8 BASE**

W/ LENS
BAB/GY8
FMW/GY8
EXN/GY8

For LED alternatives, see Bulbrite's LED catalog.

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner/Master	Beam	Color Temp.	Lumens	Average Hours	CBCP	M.O.L.	Notes pg. 95
20	MR16	GU5.3	646320	BAB/24	24	10 / 50	Flood 36°	2900K	260	2000	405	1.875"	1,2,4
			620020	BAB/120	120	10 / 50	Flood 36°	2900K	130	2000	160	1.875"	2,4
			620320	BAB/GY8	120	10 / 50	Flood 36°	2900K	130	2000	160	1.875"	2,4
35	MR16	GU5.3	646135	FRB/24	24	10 / 50	Spot 12°	2900K	370	2000	3600	1.875"	D,1,2,4
			646335	FMW/24	24	10 / 50	Flood 36°	2900K	420	2000	1000	1.875"	1,2,4
			620035	FMW/120	120	10 / 50	Flood 36°	2900K	320	2000	360	1.875"	2,4
		GY8	620335	FMW/GY8	120	10 / 50	Flood 36°	2900K	320	2000	360	1.875"	2,4
50	MR16	GU5.3	646150	EXT/24	24	10 / 50	Spot 12°	2900K	710	2000	6000	1.875"	1,2,4
			646350	EXN/24	24	10 / 50	Flood 36°	2900K	750	2000	1845	1.875"	1,2,4
			620050	EXN/120	120	10 / 50	Flood 36°	2900K	560	2000	600	1.875"	2,4
		GY8	620350	EXN/GY8	120	10 / 50	Flood 36°	2900K	560	2000	600	1.875"	2,4