



T12 U-Shaped 6"



Circline 4-Pin T9



T12 RDC

RAPID START LAMPS

CURVALUME® Standard Rapid Start Lamps – U-Shaped, 6" Leg Spacing

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life @3hrs/start	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean @25°C/77°F	Symbols & Footnotes
40	T12	22.5	22.6	Med Bipin	24082	FB40/D41/6	12	18000	4100	70	3050	2745	Ⓔ CRI 30,31,33,48

Circline T9 Rapid Start Lamps

Nominal Wattage	Bulb	Outside Diameter (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life @3hrs/start (@12hrs/start)	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean @25°C/77°F	Symbols & Footnotes
20	T9	6.25 - 6.75	4 PIN	20155	FC6T9/WW/RS	12	8000	3000	52	800	696	31,33,42,48
				20156	FC6T9/CW/RS	12	8000	4200	60	750	653	31,33,42,48
22	T9	8.00 - 8.50	4 PIN	20088	FC8T9/WW/RS	12	12000	3000	52	1050	914	31,33,42,48
				20209	FC8T9/DSW/RP	6	12000	3000	70	1100	990	CRI 31,33,42,48
				20151	FC8T9/CW/RS/6 PACK	6	12000	4200	60	1050	914	31,33,42,48
				20148	FC8T9/CW/RS	12	12000	4200	60	1050	914	31,33,42,48
				20080	FC8T9/D/RS	12	12000	6500	76	900	783	CRI 31,33,42,48
				20210	FC8T9/830/EL	6	10000	3000	80	1850	1591	CRI 31,33,40,49,79,81
32	T9	11.5 - 12.0	4 PIN	20233	FC12T9/DSW/RP	6	15000	3000	70	2100	1806	CRI 31,33,42,48
				20037	FC12T9/WW/RS	12	15000	3000	52	1950	1697	31,33,42,48
				20143	FC12T9/CW/RS/6 PACK	6	15000	4200	60	1925	1675	31,33,42,48
				20142	FC12T9/CW/RS	12	15000	4200	60	1925	1675	31,33,42,48
				20030	FC12T9/D/RS	12	15000	6500	76	1650	1436	CRI 31,33,42,48
				20057	FC16T9/WW/RS	12	18000	3000	52	2800	2436	31,33,42,48
40	T9	15.6 - 16.0	4 PIN	20132	FC16T9/CW/RS	12	18000	4200	60	2750	2393	31,33,42,48
				20072	FC16T9/D/RS	12	18000	6500	76	2350	2045	CRI 31,33,42,48

High Output (800mA) SUPERSAVER® Rapid Start Lamps

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life @3hrs/start	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean @25°C/77°F	Symbols & Footnotes
55	T12	48	46	Recessed DC	25137	F48T12D35/HO/SS	30	12000	3500	70	3750	3375	CRI 27,31,33,97
95	T12	96	93.91	Recessed DC	25011	F96T12/WW/HO/SS	15	12000	3000	52	7700	6237	Ⓔ 27,31,33,97
					25024	F96T12/D35/HO/SS	15	12000	3500	48	8350	7515	Ⓔ CRI 27,31,33,97
					25023	F96T12/D41/HO/SS	15	12000	4100	70	8350	7515	Ⓔ CRI 27,31,33,97
					25025	F96T12/LW/HO/SS	15	12000	4150	48	8000	6480	Ⓔ 27,31,33,97
					25010	F96T12/CW/HO/SS	15	12000	4200	60	8000	6480	Ⓔ 27,31,33,97
					25001	F96T12/CW/HO/SS/ECO	15	12000	4200	60	8000	6480	Ⓔ 27,31,33,76,97

High Output (800mA) Standard Rapid Start Lamps

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life @3hrs/start	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean @25°C/77°F	Symbols & Footnotes
25	T12	18	15.91	Recessed DC	25303	F18T12/DSGN50/HO	30	9000	5000	90	850	740	CRI 31,33,48
35	T12	24	21.91	Recessed DC	25313	F24T12/CW/HO	30	9000	4200	60	1650	1337	31,33,48
					25312	F24T12/DSGN50/HO	30	9000	5000	90	1200	1044	CRI 31,33,48
					25314	F24T12/D/HO	30	9000	6500	76	1400	1134	CRI 31,33,48