

Version	2.1	Date	1/26/2025
Prepared By			


PRODUCT SPECIFICATION			
Category	Wall Pack		
Item Number	9456		
Stock Code	FXTWP100SW/CCT3/BZ-PHO		
Mounting	Wall Mount		
Housing Color	Bronze		
PICTURE			

ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	60 / 80 / 100	Replacement Wattage (W)	400-750
Tested Wattage (W)	100		
Input Voltage (V)	120-277V		
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV
Input Current (A)	0.5/0.67/0.84	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	-
THD	<20%	Photocell	Included

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	9,000	CCT (K)	3CCT (30/40/50K)
	11,600		
	14,500		
Efficacy (lm/w)	145	Beam Angle (°)	Forward Throw
CRI	>80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40°F ~ 122°F
Storage Temperature (°F)	-40°F ~ 140°F
IP Rating	IP65
Rated Life (Hrs)	50,000
Warranty (Yrs)	5

ACCESSORIES		
Item #	Stock Code	Description
P10234	SEN-MC605V-D	Microwave Motion Photocell Sensor
P10403	CVR-TWP-MEDIUM/BZ	Cut-Off Shield-Bronze (medium)
P10003	LENS-TWP-PC-MEDIUM	Plastic Lens with Gasket (medium)
P10000	LENS-TWP-MEDIUM	Borosilicate Glass Lens with Gasket (medium)
P10004	WG-TWP-MEDIUM	Wire Guard (medium)

PRODUCT DIMENSIONS			
Width- in / (mm)	14.30"	363	
Height- in / (mm)	9.20"	234	
Depth- in / (mm)	7.69"	195	
EPA (ft²)	-		
Weight (lbs)	9.26		
Mounting Height (ft)	-		
Cable Length (ft)	-		

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	5.1 Premium	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS