

Accessories

Accessories

CATALOG NUMBER	DESCRIPTION	
KTSP-10KV	External surge protector, input voltage: 120-277V, maximum peak current: 10kV, IP65 Rated	
KT-ADAPTER-E39-E26	Socket base adapter allowing an E26 base lamp to be used in an E39 socket	
KTAT-150-480-277-OC	480V to 277V step-down auto-transformer, open core	
KTAT-250-480-277 /A	480V to 277V step-down auto-transformer	



At Keystone, the customer always comes first.
We're determined to go above and beyond for you.

[Your Trusted Partner]

High Voltage



Features & Benefits

- Non-isolated autotransformer
- For use with T5, T8, LED, CFL, or electronic HID ballasts operating at 277V input voltage
- Thermally protected
- UL and cUL 5085 approved
- 5-year limited warranty



High Voltage

High Voltage

CATALOG NUMBER	INPUT VOLTAGE	INPUT CURRENT AT MAX LOAD	INPUT CURRENT AT NO LOAD	OUTPUT VOLTAGE	MAX LOAD	MAX OUTPUT CURRENT	CONSTRUCTION
KTAT-150-480-277-OC	347V	0.45A	0.06A	240V	125VA	0.52A	Open core, flying leads
				277V	150VA	0.54A	
	480V	0.33A	0.05A	240V	125VA	0.52A	
				277V	150VA	0.54A	
Length	2.76"						
Width	2.32"						
Height	1.93"						

CATALOG NUMBER		INPUT VOLTAGE	INPUT CURRENT AT MAX LOAD	INPUT CURRENT AT NO LOAD	OUTPUT VOLTAGE	MAX LOAD	MAX OUTPUT CURRENT	CONSTRUCTION
KTAT-250-480-277 /A		347V	0.57A	0.11A	200V	180VA	0.90A	Fully enclosed, flying leads
		480V	0.57A	0.16A	277V	250VA	0.90A	
Length	9.45"							
Width	1.70"							
Height	1.20"							

CATALOG NUMBER		INPUT VOLTAGE	INPUT CURRENT AT MAX LOAD	INPUT CURRENT AT NO LOAD	OUTPUT VOLTAGE	MAX LOAD	MAX OUTPUT CURRENT	CONSTRUCTION
KTAT-250-480-277 /SF		347V	0.57A	0.11A	200V	180VA	0.90A	Fully enclosed, single flex
		480V	0.57A	0.16A	277V	250VA	0.90A	
Length	11.73"							
Width	1.70"							
Height	1.22"							

CATALOG NUMBER		INPUT VOLTAGE	INPUT CURRENT AT MAX LOAD	INPUT CURRENT AT NO LOAD	OUTPUT VOLTAGE	MAX LOAD	MAX OUTPUT CURRENT	CONSTRUCTION
KTAT-375-480-277 /A		347V	0.86A	0.11A	200V	270VA	1.35A	Fully enclosed, flying leads
		480V	0.86A	0.21A	277V	375VA	1.35A	
Length	11.70"							
Width	1.70"							
Height	1.20"							

CATALOG NUMBER		INPUT VOLTAGE	INPUT CURRENT AT MAX LOAD	INPUT CURRENT AT NO LOAD	OUTPUT VOLTAGE	MAX LOAD	MAX OUTPUT CURRENT	CONSTRUCTION
KTAT-375-480-277 /SF		347V	0.86A	0.11A	200V	270VA	1.35A	Fully enclosed, single flex
		480V	0.86A	0.21A	277V	375VA	1.35A	
Length	12.50"							
Width	2.30"							
Height	1.27"							