MR8 & MR11

GU4, D.C. Bayonet - 6V, 12V, 24V

- Provides UV protection
- Filament types include C-6, C-8, and CC-8
- Ideal for commercial use in retail displays, showcases or exhibits

MR8 12V	MR11 6V	MR11 12V	MR11 12V	MR11 24V	MR11 12V
W/ LENS 12MR8LN 20MR8LN 20MR8LW 35MR8LN	**W/ LENS** 5MR11NF/6 10MR11NF/6	FTB FTC FTD FTE FTF FTH	**W/ LENS** FTB/L FTC/L FTD/L FTE/L FTH/L 5MR11NF/12 10MR11NF/12	**W/ LENS** FTB/24 FTC/24	FST **W/ LENS** FST/L

For LED alternatives, see Bulbrite's LED catalog.

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner/ Master	Beam	Color Temp.	Lumens	Average Hours	CBCP	M.O.L.	Notes pg. 95
5	MR11	GU4	**642065**	**5MR11NF/6**	6	10 / **50**	N. Flood 18°	2900K	26	2000	50	1.25"	1,2,4
			642025	**5MR11NF/12**	12	10 / **50**	N. Flood 18°	2900K	55	2000	120	1.25"	1,2,4
10	MR11	GU4	**642061**	**10MR11NF/6**	6	10 / **50**	N. Flood 18°	2900K	90	2000	150	1.25"	1,2,4
			642021	**10MR11NF/12**	12	10 / **50**	N. Flood 18°	2900K	125	2000	350	1.25"	1,2,4
12	MR8	GU4	**648012**	**12MR8LN**	12	10 / **50**	Spot 9°	2900K	80	2000	1800	1.375"	1,2,4
20	MR8	GU4	**648020**	**20MR8LN**	12	10 / **50**	Spot 10°	2900K	150	2000	1700	1.375"	1,2,4
			648120	**20MR8LW**	12	10 / **50**	N. Flood 23°	2900K	155	2000	800	1.375"	1,2,4
	MR11	GU4	**642120**	**FTB**	12	10 / **50**	Spot 10°	2900K	235	2000	1500	1.25"	1,2,4
			642220	**FTC**	12	10 / **50**	N. Flood 16°	2900K	255	2000	500	1.25"	1,2,4
			642320	**FTD**	12	10 / **50**	Flood 36°	2900K	255	2000	500	1.25"	1,2,4
			642122	**FTB/L**	12	10 / **50**	Spot 10°	2900K	235	2000	1300	1.25"	1,2,4
			642222	**FTC/L**	12	10 / **50**	N. Flood 16°	2900K	255	2000	450	1.25"	1,2,4
			642322	**FTD/L**	12	10 / **50**	Flood 36°	2900K	255	2000	450	1.25"	1,2,4
			649120	**FTB/24**	24	10 / **50**	Spot 10°	2900K	180	2000	1750	1.25"	D,1,2,4
			649220	**FTC/24**	24	10 / **50**	N. Flood 16°	2900K	265	2000	720	1.25"	1,2,4
		BA15d	**643220**	**FST**	12	10 / **50**	N. Flood 16°	2900K	255	2000	500	1.625"	1,2,4
			643221	**FST/L**	12	10 / **50**	N. Flood 16°	2900K	255	2000	450	1.625"	1,2,4
35	MR8	GU4	**648035**	**35MR8LN**	12	10 / **50**	Spot 13°	2900K	275	2000	2300	1.25"	D,1,2,4
	MR11	GU4	**642135**	**FTE**	12	10 / **50**	Spot 10°	2900K	500	2000	2500	1.25"	1,2,4
			642235	**FTF**	12	10 / **50**	N. Flood 16°	2900K	510	2000	800	1.25"	1,2,4
			642335	**FTH**	12	10 / **50**	Flood 36°	2900K	510	2000	800	1.25"	1,2,4
			642137	**FTE/L**	12	10 / **50**	Spot 10°	2900K	200	2000	2200	1.25"	D,1,2,4
			642337	**FTH/L**	12	10 / **50**	Flood 36°	2900K	510	2000	720	1.25"	1,2,4